

[NMS Releases](#) >

NMS Release 1-1200

Release Date

2010-06-30

Highlight

- Option to send CDR over SBus
- Option to send Territory, Domain, User, Device, Connection, Dial Plan, Dial Policy and Route configuration over SBus
- Passthrough 488/ACK while re-INVITING
- Correct crash from when packet object got accidentally deleted from left over handles

Resolved Issues

Issue #	Issue Type	Descriptions
NS001459	Deflect	One Way Audio Call Monitoring
NS001534	Feature	Smarter Defaulting techniques
NS001547	Feature	add "show route" button to call history
NS001551	Feature	Do not kill call (send bye) on acceptance of sip 488
NS001555	Deflect	Extra quote in "nc" field in Authentication response
NS001563	Feature	add ui_config knob for "dial_match" in domain
NS001572	Deflect	Failure to transmit ACK in response to 488
NS001582	Deflect	SQL for Domain update need to escape for quote

Database Changes

Table	Fields	Descriptions
domains_config	mksdir	If 'yes' create subscriber directory

Changes

NCS CPP Code

No change.

NMS CPP Code

Issue #	Descriptions
---------	--------------

	(1-1200x1) Send/Receive Domain, User, Device, Connection, Dial Plan, Dial Policy and Route configuration over SBus
NS001459	(1-1200x2) Correct the making of OK Response to re-INVITE during Audio Monitoring state.
NS001551	(1-1200x2) Allow 415, 488 and 491 Response to pass through and keep the call connected during Re-Invite after Talking start
	(1-1200x2) Applied the "Authentication User" as the User part in the From-URI, To-URI and Contact for outbound REGISTER
	(1-1200x2) Added authentication retry limit to outbound REGISTER
NS001555	(1-1200x2) Correct syntax error for the "nc" field in the Authentication header for a Authentication challenge response
	(1-1200x3) Add `domains_config`.`mkmdir` to select auto creation of subscriber directories for the corresponding domain.
NS001572	(1-1200x4) UAS State Completed propagate ACK to Session layer
	(1-1200x5) Correct CDR's `route_to` and `route_class` for S-Ring not answered by the last rung call leg
	(1-1200x6) NULL packet handle hold by UAS/UAC transaction after they are returned to Pool to prevent accidental of reflush packet object that might already been re-assigned.
NS001582	(1-1200x7) Added special character escape to Domain update SQL

UI Code

Issue #	Descriptions
	(1-1200x1) SBusReciver for CDR and descriptions for Territory, Dial Plan and Dial Policy
NS001547	(1-1200x1) Added option to show Route in CDR
	(1-1200x2) Add "Make Sub Dir" option to select auto creation of User directories for the corresponding Domain.
NS001534	(1-1200x3) When adding user, initialize configuration from Domain's "domain" user before applying Default
NS001563	(1-1200x4) Added UI Config \$UI_SHOW_DOMAIN_DIAL_MATCH and \$UI_SHOW_DOMAIN_MAKE_UDIR
	(1-1200x5) Added Pop-Ups to show Orig and Term Info in CDR
	Added System Update To 1-1200 <ul style="list-style-type: none"> • Add `domains_config`.`mkmdir`

Responder

No change.

Upgrade Procedures

- "Upload UI" Nms_UI_1-1200.tar.gz

- "Code Select" UI "Nms_UI_1-1200"
- From tac login apply "System Update"- "To 1-1200"

- "Upload Code" nms-1-1200-f12_64.tar.gz
- "Code Select" "nms-1-1200-f12_64"